




Product Specification &

SAFETY DATA SHEET

CHIP / EC FORMAT 91/155/EEC AMD 93/112/EC AMD 2001/58/EC



B140
DRI PRO

SECTION 1: IDENTIFICATION OF THE PREPARATION AND COMPANY

Product Name: DRI PRO **Product Code:** B140
Manufacturer: Prochem Europe Ltd., Oakcroft Road, Chessington, Surrey KT9 1RH, UK. Telephone No: 020 8974 1515 (UK) +44 20 8974 1515 (EC) Chemical Product Manager E, H & S
Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department, who may seek advice from the **UK National Poisons Information Service**, where our full product details are held.

Product Description & Directions For Use:

A special blend of safe solvent, surfactant and fragrance for professional cleaning of fine fabrics which cannot be wet cleaned. Dri Pro is formulated for use in approved solvent extraction equipment or application by hand according to label directions. Vacuum fabric thoroughly to remove loose soil and dust.
Always pretest fabric with Dri Pro for colour fastness and texture change in an inconspicuous area before proceeding.
Ensure adequate ventilation, no smoking and prohibit people and pets from the cleaning area. Wear solvent resistant gloves, safety glasses and for extended periods of exposure, wear an approved solvent cartridge respirator.
 Apply according to machine operating instructions, ensuring that machine exhaust hose is properly vented to outside atmosphere. For hand cleaning application, spray onto fabric, brush heavily soiled areas if required, then blot or wipe fabric with clean white towel and allow fabric to dry completely before re-use.

SECTION 2: COMPOSITION / INFORMATION ON INGREDIENTS

SUBSTANCE	RISK (See Section 16)	EINECS NO.	CAS NO.	% W/W (EC RANGE)
Aliphatic hydrocarbon	Xn R65 R66	649-275-00-4	64741-65-7	More than 30%
Anionic surfactant	-	-	-	Less than 1%
Fragrance	-	-	-	Less than 1%

SECTION 3: HAZARDS IDENTIFICATION

Classification: Harmful: May cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.
Eye Contact: Contact with liquid or high concentration of vapour may cause slight eye irritation.
Skin Contact: Prolonged or repeated contact will dry the skin and cause irritation and possible dermatitis.
Inhalation: Excessive exposure above recommended level may cause headache and breathing irritation.
Ingestion: Low oral toxicity. May be harmful or fatal if swallowed and aspirated into lungs.
Environment: Not inherently biodegradable. May bioaccumulate. Low hazard to animal and aquatic life.

SECTION 4: FIRST AID MEASURES

Eye Contact: Flush immediately with water for 10 minutes holding eyelids apart, then seek medical attention.
Skin Contact: Wash skin with soap and water. Use shower if necessary. Seek medical attention if irritation persists.
Inhalation: Remove from exposure. Keep warm and at rest. If breathing is difficult, obtain immediate medical assistance and give oxygen.
Ingestion: If swallowed, **DO NOT INDUCE VOMITING.** Seek medical advice immediately and show the container or label.

SECTION 5: FIRE FIGHTING MEASURES

Extinguishing Media: Use water, carbon dioxide, dry powder extinguisher, foam, or water spray to keep containers cool.
Fire/Explosion Hazards: Vapours heavier than air. Flash point 60°C. Explosive limits for hydrocarbon in air 0.6% - 6% v/v.
Decomposition Products: Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids and other unidentified thermal decomposition products from this product or its packaging.
Special Protective Equipment: Self contained breathing apparatus and full protective clothing.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Protection: Avoid contact with liquid. Ventilate area and remove all sources of ignition. Wear protective clothing, rubber gloves, chemical splash goggles. Under severe conditions use respiratory protection or breathing apparatus.
Containment and Disposal: Prevent liquid from entering drains or water courses. Advise water authority if large amount of solvent enters drain or water course. Contain and absorb with sand, earth or vermiculite. Do not use combustible materials such as sawdust. Transfer to suitable container for disposal by licensed contractor at legal waste disposal site. Wash area of spillage with plenty of water and detergent.

SECTION 7: HANDLING AND STORAGE

Handling Precautions: Wear solvent resistant rubber gloves and safety glasses when handling liquid. Ensure adequate ventilation and eliminate all ignition sources - no smoking. Wear approved respirator for extended applications.
Storage Precautions: Store in a cool dry ventilated area away from any source of heat, ignition, static electricity or direct sunlight. Maximum recommended storage temperature is 30°C. Keep away from strong acids, alkalis and oxidising agents. Keep out of reach of children. Keep in original container.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits: Occupational exposure limits not assigned by HSE EH/40 or ACGIH. Suggested OES-LTEL 300ppm.
Environmental Controls: For additional guidance, contact ENVIROWISE at www.envirowise.gov.uk or telephone 0800 585794
Eye Protection: Side shield safety glasses or goggles are recommended when handling or during spraying.
Protective Clothing: Standard work clothing and solvent resistant NBR rubber gloves. Protective gloves should be

inspected for wear before use and replaced regularly in accordance with the manufacturers specifications.

Respiratory Protection: For situations where recommended exposure limits may be exceeded or where there is a risk of inhalation of fine spray mists, an approved organic solvent twin cartridge face mask with appropriate filter (e.g. 3M 6000 Series half-mask respirator) should be used.

Ventilation: Ensure good air circulation and ventilation in enclosed areas. Use forced air fans if necessary.

Hygiene: Wash hands and clothing after use or spill. Do not eat or drink when handling solvent. DO NOT SMOKE IN WORK AREA.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Colour/State: Clear colourless liquid solvent

Odour: Lemon

pH Concentrate: Neutral **pH Diluted:** Not applicable

Boiling Point / Range °C: 187 to 215 @ 760mmHg

Flash Point °C: 60 **Method:** PM Closed cup

Flammability Limit %: 0.6 to 6

Explosive Properties: Not determined

Oxidising Properties: Not applicable

Vapour Pressure: 100Pa @ 20°C

Relative Density (Water = 1): 0.761 @ 15°C

Solubility: Insoluble in water. Soluble in hydrocarbons

Partition Coefficient (N-octanol / Water): Not determined

Viscosity: Not determined

Vapour Density: 4.5

Evaporation Rate: 0.09 (BuAc = 1)

% Active: 100

% Solids: Not applicable

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable

Conditions to Avoid: Heat, ignition sources, static build-up, direct sunlight.

Incompatibility (Materials to Avoid): Strong oxidising or alkaline agents.

Hazardous Decomposition Products: Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids and other unidentified thermal decomposition products from this product or its packaging.

SECTION 11: TOXICOLOGICAL INFORMATION

Eye Contact: Liquid and vapour (at higher temperatures and concentrations) may cause transient eye irritation effects.

Skin Contact: Prolonged exposure will cause defatting and may produce a dry, scaly and fissured dermatitis.

Inhalation: Excessive exposure to hydrocarbon vapour at high temperatures may cause central nervous depression. Acute overexposure to inhalation of spray mist may cause lung congestion and oedema.

Ingestion: Low oral toxicity. Large amounts may cause irritation of digestive tracts, vomiting and diarrhoea followed by CNS effects. Chemical pneumonia and pulmonary oedema if quantities are aspirated into lungs.

Acute and Chronic Effects:

Acute Toxicity: Not established

Corrosivity / Irritation: Skin, eye and respiratory

Sensitisation: None Known

Repeated Dose Toxicity: Not established

Mutagenicity: None

Carcinogenicity: None

Teratogenicity: None

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: Low aquatic and mammalian toxicity.

Mobility: Will float on water and evaporate slowly. Dissolved material adsorbs strongly to soil and sediment and is not mobile. Product remaining on soil surface evaporates within one day.

Persistence and Degradability: Not inherently biodegradable. Oxidises rapidly by photochemical reactions in air. Integrated environmental half-life expected to be 10 - < 100 days. The major packaging materials of polyethylene and fibreboard are recyclable.

Bioaccumulative Potential: Has potential to bioaccumulate.

Other Effects: None known or no relevant data available for substances in this preparation.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste cleaning solvent effluent should be transferred to suitable containers and disposed of in accordance with special waste regulations (Special Waste Regulations 1996, Environment Act 1995 and Environmental Protection Act 1990). Do not allow solvent to enter drains. Empty containers should be rinsed with water then crushed and disposed of at legal waste disposal site. Contact local Environment Agency office for waste holder requirements.

SECTION 14: TRANSPORT INFORMATION

UN No: 3295

Classification: Flammable Liquid

Proper Shipping Name: Hydrocarbons, Liquid, N.O.S. (Solvent Naphtha solution)

Packing Group: III

Road (ADR): Class 3

Sea (IMDG): Class 3

Air (ICAO / IATA): Class 3

Rail (RID): Class 3

SECTION 15: REGULATORY INFORMATION

Classification: Xn HARMFUL

Risk Phrases

R65 Harmful: May cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

Safety Phrases

S2 Keep out of reach of children.

S23 Do not breathe vapour / spray.

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S37 Wear suitable gloves.

S38 In case of insufficient ventilation, wear suitable respiratory equipment.

S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

The information given has been compiled with reference to the **CHEMICALS (HAZARD INFORMATION AND PACKAGING FOR SUPPLY) REGULATIONS (CHIP 3) 2002** (as amended), the **CONTROL OF SUBSTANCES HAZARDOUS TO HEALTH REGULATIONS (COSHH) 2002** (as amended) and the **MANAGEMENT OF HEALTH AND SAFETY AT WORK REGULATIONS 1999** (as amended).

This safety data sheet does not constitute the users own assessment of workplace risk as required by other health and safety regulations.

SECTION 16: OTHER INFORMATION

Risk Phrases: R65 Harmful: May cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking.

For additional information on safety, training and use of this product, contact the supplier. This product is intended for professional use only. The information given is intended to be of assistance to users but is without guarantee. Variations can occur in application and users are advised to conduct their own tests. Suggestions for use neither give nor imply any guarantee as to the intended use.

Revisions: Replaces SDS B140 Issue / Revision Date 01/08/02 Revised Sections: 1, 8, 9, 14, 15